



## Bid Notice Abstract

### Request for Quotation (RFQ)

**Reference Number** 7796679  
**Procuring Entity** PHILIPPINE RICE RESEARCH INSTITUTE  
**Title** Procurement of Electronic parts and supplies for the development of the robotic seeder  
**Area of Delivery** Metro Manila, Nueva Ecija

<b>Solicitation Number:</b>	2021-06-1752	<b>Status</b>	<b>Pending</b>
<b>Trade Agreement:</b>	Implementing Rules and Regulations		
<b>Procurement Mode:</b>	Negotiated Procurement - Small Value Procurement (Sec. 53.9)	<b>Associated Components</b>	1
<b>Classification:</b>	Goods	<b>Bid Supplements</b>	0
<b>Category:</b>	Electronic Parts and Components		
<b>Approved Budget for the Contract:</b>	PHP 127,200.00	<b>Document Request List</b>	0
<b>Delivery Period:</b>	30 Day/s		
<b>Client Agency:</b>		<b>Date Published</b>	26/06/2021
<b>Contact Person:</b> Abegail Tirante Donayre Admin Officer V Maligaya Science City of Muñoz Nueva Ecija Philippines 3119 63-44-4560650 63-44-4560650 ppmu.pmd@gmail.com		<b>Last Updated / Time</b>	25/06/2021 09:16 AM
		<b>Closing Date / Time</b>	29/06/2021 17:00 PM

#### Description

Item No. Quantity Unit Item and Description  
1 2 piece " High Power DC Gear Motor  
Type: Brushed DC  
Power: 1000 Watts  
Voltage: 48 Volts DC  
Speed Reduction: Planetary Gear  
Speed: 500 rpm"  
2 4 piece Brushed DC Motor Driver Module Operating Voltage: DC 7V to 58V Maximum Motor Current: 25A continuous, 60A peak 5V output for the host controller (250mA max) PWM/DIR Inputs compatible with 1.8V, 3.3V, 5V, 12V and 24V logic (Arduino, Raspberry Pi, PLC, etc) PWM frequency up to 40kHz (Output frequency is fixed at 16kHz)  
3 4 piece " Microcontroller Package  
Broadcom BCM2835, 1GHz ARM11 single-core processor  
SDRAM: 512MB RAM  
Wireless connectivity: 802.11 b/g/n wireless LAN  
Bluetooth 4.1, Bluetooth Low Energy (BLE)  
40PIN pre-soldered GPIO headers  
Micro SD card slot  
Mini-HDMI port (1080p60 video output)  
Micro-USB power  
Micro-USB OTG port  
CSI camera connector  
Composite video header  
Composite reset header  
Dimension: 65mm x 30mm x 11.6mm  
Mini HDMI to HDMI Adapter  
Micro USB OTG Cable  
Micro SD Card 16GB  
Power adapter US standard 5V/3A micro  
USB type A plug to micro B plug cable  
USB HUB HAT"  
4 4 piece "Advance Microcontoller Package  
Broadcom BCM2711, Quad core Cortex-A72 (ARM v8) 64-bit SoC @ 1.5GHz  
SD RAM: 8GB LPDDR4-3200 SDRAM (depending on model)  
2.4 GHz and 5.0 GHz IEEE 802.11ac wireless, Bluetooth 5.0, BLE  
Gigabit Ethernet  
2 x USB 3.0 ports; 2 x USB 2.0 ports.  
2 x micro-HDMI ports (up to 4kp60 supported)  
2-lane MIPI DSI display port  
2-lane MIPI CSI camera port  
4-pole stereo audio and composite video port H.265 (4kp60 decode), H264 (1080p60 decode, 1080p30 encode)  
OpenGL ES 3.0 graphics  
Micro-SD card slot for loading operating system and data storage  
5V DC via USB-C connector (minimum 3A\*)

5V DC via GPIO header (minimum 3A*) Power over Ethernet (PoE) enabled (requires separate PoE HAT) 1xCASE Black 1xOfficial USB-C Power Supply 1xMicro HDMI to Standard HDMI 1m Cables 1x16GB Class10 microSD Card 1xSet of Heatsink 1xT-Cobbler GPIO Breakout compatible with Raspberry Pi 1x3.5 in. Touchscreen TFT LCD for Raspberry Pi 3 4 RPi with Stylus Pen" 5 4 piece "Camera Module without Infrared CutOff Filter 8 megapixel native resolution sensor-capable of 3280 x 2464 pixel static images Supports 1080p30, 720p60 and 640x480p90 video Size 25mm x 23mm x 9mm No IR Filter with Blue Filter Fixed focus lens on-board 150mm CSI camera cable included Weight just over 3g Can connect to a Raspberry Pi board via a short ribbon cable" 6 4 piece "Low Speed DC Motor Voltage Range : 12-24V Nominal Voltage: 24V No Load Speed: 90 r/min No Load Current: 500 mA Max. Torque: 27 kg. cm Power: 35W StallTorque: 135kg. cm Stall Current: 20A Reduction Ratio: 1:91 Weight: 775g" 7 1 piece "GPS-RTK2 Board Concurrent reception of GPS, GLONASS, Galileo and BeiDou Receives both L1C/A and L2C bands Voltage: 5V or 3.3V but all logic is 3.3V Current: ~35mA (varies with constellations and tracking state) Time to First Fix: 25s (cold), 2s (hot) Max Navigation Rate: PVT (basic location over UBX binary protocol) - 25Hz RTK - 20Hz Raw -25Hz Horizontal Position Accuracy: 2.5m without RTK 0.010m with RTK Max Altitude: 50km (31 miles) Max Velocity: 500m/s (1118mph) Dimensions: 43.5mm x 43.2mm (1.71in x 1.7in) 2x Qwiic Connectors" 8 4 piece "Camera Module with Infrared CutOff Filter 8 megapixel native resolution sensor-capable of 3280 x 2464 pixel static images Supports 1080p30, 720p60 and 640x480p90 video Size 25mm x 23mm x 9mm Fixed focus lens on-board 150mm CSI camera cable included Weight just over 3g Can connect to a Raspberry Pi board via a short ribbon cable" <b>Other Information</b> Pls. send your Quotation to:  Contact Person: Mighty Jemuel Sotto Email: mjc.sotto@mail.philrice.gov.ph Contact No: (044) 456 0650 loc. 660/ 09975028500
--

<b>Created by</b>	Abegail Tirante Donayre
<b>Date Created</b>	25/06/2021

The PhilGEPS team is not responsible for any typographical errors or misinformation presented in the system. PhilGEPS only displays information provided for by its clients, and any queries regarding the postings should be directed to the contact person/s of the concerned party.