



Philippine Rice Research Institute


DA-PhilRice Agusan Branch Station
Basilisa, RTRomualdez, 8611 Agusan del Norte


Date: 2025-06-05

REQUEST FOR QUOTATION

Sir/Madam:

Please quote your best offer for the item/s listed below, **subject to the Terms and Conditions** provided. Submit your quotation duly signed by you or your duly authorized representative not later than **June 13, 2025** to rockyypagaduan@gmail.com or send via fax or drop at PMU box at Procurement Management Unit (PMU), Basilisa, RTRomualdez, 8611 Agusan del Norte. For any clarification you may call/send through fax to **09489306844** or PMU no. **09088808976**.


Rocky Padaduan
BUYER/CANVASSER


Kharen R. Galvez
AO II

INSTRUCTIONS:

1. Accomplish this RFQ correctly and accurately.
2. Please do not leave any blank items. Indicate "0" if the item being offered is for free and "NO BID" if no offer.
3. Do not alter the contents of this form in any way.
4. All technical specifications are mandatory. Fill in the column designated for technical specifications of your offer, you may specify the brand and model if applicable. Use additional sheet if needed or attach a brochure.
5. Failure to follow these instructions will disqualify your quotation.
6. NEW suppliers/bidders are required to submit a photocopy/e-copy of valid Mayor's Business Permit, BIR Registration 2303, DTI/SEC/CDA Registration (whichever is applicable), valid PhilGEPS Registration Number, and valid PCAB License (if applicable) together with their quotations. Please disregard if you have submitted an updated copy/ies to PMD. This shall be subjected to validation.
7. Award of items in this RFQ will be: per item per lot.
8. For awarding per lot, supplier shall provide quotation for all the items, otherwise the quote will be disregarded.
9. Awarding per item accepts partial bids.

Procurement Project Title: Procurement of Surveillance Camera (CCTV) for PhilRice Agusan
 Procurement Project No.: SVP-036B PR No.: 2025-06-0085
 Approved Budget of the Contract: 515,000.00

| Item No. | Quantity | ABC | Unit | Item and Description | Unit Price | Total Amount |
|----------|----------|------------|------|--|--------------|--------------|
| | | | | Per Request | Offer | |
| 1 | 1 | 515,000.00 | lot | ICT equipment, Surveillance Device CCTV Surveillance Camera *Network Video Recorder (NVR): 32-channel 4K NVR with 1.5U rack-mount chassis, supports up to 4 HDDs (6TB each), 256Mbps bandwidth, H.265+/H.264 decoding, and high-resolution recording up to 12MP. Features dual HDMI/VGA outputs, 2 Gigabit LAN ports, PoE support, and wide video output compatibility up to 4K/60Hz *PoE Network Switch: 16+4 Port Gigabit PoE switch with 12 PoE (30W) and 4 Hi-PoE (90W) ports, 2 RJ45, and 2 fiber ports. Supports IEEE 802.3 standards, 6KV surge protection, up to 300m long-range, PoE watchdog, port isolation, wire-speed forwarding, and durable metal housing *Hard Disk Drive: 8TB 3.5" internal surveillance HDD with 256MB cache, SATA 6Gb/s. 245MB/s sustained | | |

Better Rice Communities.

Tel: (85) 806-0463; Email: agusan.station@mail.philrice.gov.ph
 DA-PhilRice Field Office, CMU Campus, Sayre Highway, Musuan, Maramag, 8714 Bukidnon
 Mobile: 0909-822-9813
 Email: philricefocmu.2019@gmail.com
 Websites: www.philrice.gov.ph, www.pingvrice.com
 Social Media: www.facebook.com/philrice.aes





Philippine Rice Research Institute

DA-PhilRice Agusan Branch Station
Basilisa, RTRomualdez, 8611 Agusan del Norte

analytics, deep learning servers, cloud storage, RAID, and JBOD. Optimized for high-volume surveillance data in NVR systems

*CCTV Camera: 4MP outdoor bullet IP camera with 24/7 full-color night mode, fixed lens (2.8mm/4mm/6mm), H.265+/H.264+ encoding, 120dB WDR, 3D DNR, IP67 weatherproof, and 0.0014 Lux low-light performance. Supports DC12V & PoE, fully compatible with HikVision NVR

*CCTV Camera: 4MP IP turret camera with 24/7 full-color night mode, built-in mic, microSD slot (up to 128GB), fixed lens (2.8mm/4mm/6mm), 30m warm white LEDs, 120dB WDR, 3D DNR, IP67 weatherproof, low-light at 0.0014 Lux, supports DC12V & PoE, fully HikVision NVR compatible

*CCTV Camera: 4MP dome IP camera with AcuSense and DarkFighter for low-light clarity, 120dB WDR, human/vehicle detection via deep learning, built-in mic, IR up to 30m, fixed lens (2.8/4/6mm), smart events, IP67/IK10 rated, supports H.265+/H.264+, PoE/DC12V, fully HikVision NVR compatible

*CCTV Camera: 6MP fisheye IP camera with dewarping to 4-image PTZ view, 3072x2048 @30fps, IR range up to 15m, fixed lens (2.8/4/6mm), low-light performance (0 Lux with IR), built-in mic, microSD slot (up to 128GB), 3D DNR/WDR, IP66/IK10 rated PoE/DC12V, HikVision NVR compatible

*CCTV Camera: PTZ camera with HD to 4K resolution, optical/digital zoom (10x/4x/20x), full pan/tilt range and speed, wide field of view, infrared night vision, smart detection (human/vehicle), preset positions, IP66 weatherproof, multiple output options (IP/HDMI/USB/SDI), and powered via 24V AC

*Monitor: 32" LED 1920x1080p (HDMI/VGA, AOV 178°/178°, with builtin Speaker

- Note:
1. Please see attached file for other details
 2. Provision of Labor and all necessary materials (like RJ45, UTP Outdoor cable, etc.) for the installation and activation of online access
 3. Supplier must inspect the area/station to asses for necessary materials to be used/installed

TERMS AND CONDITIONS

Better Rice Communities.

Telefax: (85) 806-0463; Email: agusan.station@mail.philrice.gov.ph
DA-PhilRice Field Office, CMU Campus, Sayre Highway, Musuan, Maramag, 8714 Bukidnon
Mobile: 0909-822-9813
Email: philricefocmu.2019@gmail.com
Websites: www.philrice.gov.ph, www.pingyricerice.com
Social Media: web.facebook.com/philrice.aes





Philippine Rice Research Institute

DA-PhilRice Agusan Branch Station
Basilisa, RTRomualdez, 8611 Agusan del Norte

Delivery Period: 30 calendar days

Price Validity: 30 CD [] 45 CD [] 60 CD [✓] 90 CD [] 120 CD [] Others [] _____

Place of Delivery: Philippine Rice Research Institute-CES, Brgy. Maligaya, Science City of Munoz, Nueva Ecija
ATI Building, Elliptical Road, Diliman, Quezon City
 Others: Basilisa, RTRomualdez, 8611 Agusal del Norte

Warranty: 1 year (non-consumable supplies/Equipment) and 3 months (consumable supplies)

Payment Term: 30 calendar days

- Price quotations shall include all taxes, duties and/or levies. Deductions of 5% VAT & 1% EWT (for goods) or 5% VAT & 2% EWT (for services).
 - Price Quotations exceeding the Approved Budget for the Contract shall be rejected.
 - Award of contract shall be made to the lowest quotations (for goods and infrastructure) or, the highest rated offer (for consulting services) which complies with the minimum technical specifications and other terms and conditions stated herein
 - In case of two or more bidders are determined to have submitted the Lowest Calculated Quotation/Lowest Calculated and Responsive Quotation, the PhilRice shall adopt and employ "draw lots" or "toss coin" as the tie-breaking method to finally determine the single winning provider in accordance with GPPB Circular 06-2005.
 - Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by you or any of your duly authorized representative/s.
 - The item/s shall be delivered according to the requirements specified in the Conformed Purchase Order or Contract.
 - Goods, supplies, equipment, or work done are subject to inspection/acceptance, PhilRice reserves the right to cancel, reject, or rebid the items which do not conform with the technical specifications.
 - Liquidated damages equivalent to 1/10 of 1% per day of delay for the value of undelivered items shall be imposed. PhilRice shall rescind the contract once the cumulative amount of liquidated damages reaches ten (10) percent of the amount of contract, without prejudice to other courses of actions and remedies open to it.
 - The Bidder warrants that s/he has not given nor promised to give any money or gift to any PhilRice employee to secure this offer and to obtain an award.
 - The winning Bidder is required to submit a photocopy of Latest Income/Business Tax Return and original copy of Omnibus Sworn Statement prescribed by the GPPB before the award of the goods delivered/services rendered.
 - Payment shall be made within (30) days after 100% completion of delivery subject to submission and/or completion of supporting documents, in accordance with existing accounting rules and regulations. Please note that the corresponding bank transfer fee, if any, shall be chargeable to the contractor's/Supplier's account.
- After having carefully read and accepted the Procurement Terms & Conditions, I/We quote you on the item at prices noted above.

PRINTED NAME/SIGNATURE OF AUTHORIZED REPRESENTATIVE

Designation: _____

Company Name: _____

Business Address: _____

PhilGEPS Registration No.: _____

Telephone Number: _____

Email Address: _____

Better Rice Communities.

Telefax: (85) 806-0463; Email: agusan.station@mail.philrice.gov.ph
 DA-PhilRice Field Office, CMU Campus, Sayre Highway, Musuan, Maramag, 8714 Bukidnon
 Mobile: 0909-822-9813
 Email: philricefocmu.2019@gmail.com
 Websites: www.philrice.gov.ph, www.pingyricerice.com
 RFO Control No.: 2025-06-0038 (B)
 Social Media: Web: facebook.com/philrice.aes



1 lot Surveillance Camera (CCTV) for PhilRice Agusan

| DESCRIPTION | SPECIFICATION | UNIT PRICE | TOTAL AMOUNT |
|------------------------------|--|------------|--------------|
| Network Video Recorder (NVR) | <p>32 channel 1.5U 4K NVR Up to 1-ch@32 MP/2-ch@12 MP/16-ch@1080p decoding capacity 4 HDD for continuous video recording 2 HDMI and VGA video output interface 4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz Incoming bandwidth: 256Mbps H.265+, H265, H264+, H264 decoding format Recording Resolution: 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA /4CIF/DCIF/2CIF/CIF/QCIF Network Protocol: TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS PoE, 2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces Up to 6TB HDD capacity each 19" rack mounted 1.5U chassis</p> | | |
| PoE Network Switch | <p>16 + 4 Port Gigabit Unmanaged POE Switch 16 × gigabit PoE ports, 4 × gigabit Hi-PoE ports, 2 × gigabit RJ45 ports, and 2 × gigabit fiber optical ports. IEEE 802.3at/af/bt standard for Hi-PoE ports (Max. 90 W PoE output). IEEE 802.3at/af standard for PoE ports (Max. 30 W PoE output). IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, and IEEE 802.3z standard. 6 KV surge protection for PoE ports. Up to 300 m long-range transmission. PoE watchdog to auto detect and restart the cameras that do not respond. Port isolation to improve network security. Gigabit network access design. Wire-speed forwarding. Store-and-forward switching. Solid high-strength metal shell.</p> | | |
| Hard Disk Drive | <p>3.5" Internal Surveillance Hard Drive 8TB capacity 256MB cache, SATA, 6GB/s Transfer Rate max. (Buffer to Host) Transfer Rate sustained 245MB/s (Host to/From Drive) Pro surveillance 24x7 usage Support the heavy video data capture and analysis found in advanced AI-enabled recorders, video analytics appliances, deep learning analytics servers and cloud-based storage, including RAID and JBOD configurations. For Surveillance purposes (NVR)</p> | | |
| CCTV Camera | <p>3 Units Outdoor Bullet type CCTV Camera 4MP IP based camera 2688 × 1520 @ 30fps 2.8mm/4mm/6mm fixed lens H.265+, H.264+ 32Kbps to 16 Mbps video bit rate 0.0014 Lux @ (F1.0, AGC ON), 0 Lux with Light 24/7 Full Time Color Night Mode 120dB WDR 3D DNR DC12V & PoE (802.3af) IP67 Fully compatible with HikVision NVR</p> | | |
| CCTV Camera | <p>14 Units Turret type CCTV Camera 4MP IP based camera 2688 × 1520 @30fps 2.8mm/4mm/6mm fixed lens H.265+, H.264+ 0.0014 Lux @ (F1.0, AGC ON), 0 Lux with Light 24/7 Full Time Color Night Mode Built-in Mic Built-in micro SD/SDHC/SDC slot up to 128GB 120dB WDR 3D DNR 30m Warm white LEDs DC12V & PoE (802.3af) IP67 Fully compatible with HikVision NVR</p> | | |

| | | | |
|---|--|--|--|
| CCTV Camera | <p>15 Units Dome type CCTV camera 4 MP Acusense Fixed dome Network Camera Excellent low-light performance with powered-by-DarkFighter technology Clear imaging against strong backlight due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Built-in microphone for real-time auto security(-SU) Max. Resolution 2688 × 1520 Min. Illumination Color: 0.003 Lux @ (F1.4, AGC ON), B/W: 0 Lux with IR Image Enhancer: BLC, HLC, 3D DNR Shutter Time: 1/3 s to 1/100,000 s, Day & Night: IR cut filter, Image Sensor: 1/3" Progressive Scan CMOS Aperture: F1.4, Lens Type: Fixed focal lens, 2.8, 4, and 6 mm optional Video Compression: Main stream: H.265/H.264/H.265+/H.264+ Ethernet Interface: 1 RJ45 10 M/100 M self-adaptive Ethernet port Motion detection (human and vehicle targets classification), video tampering alarm, exception Smart Event: Line crossing detection, intrusion detection, region entrance detection, region exiting detection (support alarm triggering by specified target types (human and vehicle)) Linkage: Upload to NAS/memory card/FTP, notify surveillance center, trigger recording, trigger capture, send email, audible warning Supplement light: IR with supplement light range up to 30m DC12V & PoE (802.3af/at) IP67/IK10 water resistant and vandal proof *Fully compatible with HikVision NVR</p> | | |
| CCTV Camera | <p>2 Units Fisheye type CCTV Camera 6MP IP based camera capturing clear images even when dewarped into 4-image PTZ mode 3072 × 2048 @30fps, 1/1.8" progressive scan CMOS Built-in IR light: an IR range of 15 meters provides good visibility in low or even zero-light environments 2.8mm/4mm/6mm fixed lens H.264+ 0.05 Lux @ (F1.2, AGC ON), 0.25 Lux @ (F2.6, AGC ON), 0 Lux with IR Built-in Mic Built-in microSD/SDHC/SDXC slot, up to 128 GB 3D DNR, 3D WDR Image Enhancement: BLC/3D DNR IR Range 15 m DC12V & PoE (802.3af) IP66/IK10 water resistant and vandal proof Fully compatible with HikVision NVR</p> | | |
| CCTV Camera | <p>2 Units PTZ type CCTV Camera Resolution: Ranges from standard definition (SD) to high definition (HD) and Ultra HD (4K). Zoom: Optical zoom (e.g., 10x, 12x, 20x) and digital zoom capabilities. Pan and Tilt Range: Horizontal (pan) and vertical (tilt) movement capabilities, often expressed in degrees (e.g., ±90° pan, ±35° tilt). Pan and Tilt Speed: How quickly the camera can pan and tilt, measured in degrees per second. Field of View (FoV): The horizontal and vertical angles the camera can see, typically measured in degrees. Night Vision: Ability to capture images in low-light or dark conditions, often using infrared (IR) technology. Connectivity: Protocols like IP, HDMI, USB, and SDI for video output and control. Weatherproofing: IP rating (e.g., IP66) indicating protection against dust and water. Power: Power requirements, including voltage (e.g., 24V AC) and power consumption. Preset Positions: Ability to store and recall specific camera positions. Smart Features: Some PTZ cameras include features like smart detection (people, vehicles), voice tracking, and more.</p> | | |
| Monitor | <p>32" LED Monitor 1920x1080p (HDMI/VGA, AOV 178°/178° with builtin Speaker</p> | | |
| | <p>Provision of Labor and all necessary materials (like RJ45, UTP Outdoor cable, etc.) for the installation and activation of online access</p> | | |
| <p><i>Note: Supplier needs to inspect the area/station for necessary materials or suggested materials</i></p> | | | |